

857 UTC TESTAF

Page 1 / 2 May 2024

The TESTAF-certified pilot watch designed for professional use.



- Tested and certified to the Technical Standard for Pilot Watches (TESTAF) by the Aachen University of Applied Sciences
- Second time zone on a 24-hour basis
- · Case made of stainless steel, bead-blasted
- Case made with TEGIMENT Technology and therefore especially scratch-resistant
- · Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Functionally reliable from –45°C up to +80°C
- · Captive pilot's bezel with minute ratcheting
- · Sapphire crystal glass
- · Pressure-resistant to 20 bar
- · Low pressure resistant

The 857 UTC TESTAF was tested and certified to the the "Technical Standard for Pilot Watches" (Technischer Standard Fliegeruhren – TESTAF) by the Aachen University of Applied Sciences. This establishes its suitability for professional use as a pilot watch. It is attested to by a certificate and the "TESTAF" quality seal on the dial.

The case of the 857 UTC TESTAF has been hardened with TEGIMENT Technology to make it especially scratch-resistant. The range of technologies also includes Ar-Dehumidifying Technology for greater functional reliability and freedom from fogging and overall functional reliability at temperatures between –45°C and +80°C. The 857 UTC TESTAF features a further time measurement element: a display for a second time zone on a 24-hour basis.



Technical details

Page 2 / 2 May 2024

Mechanical Movement

- ETA 2893-2
- · Self-winding mechanism
- · 21 bearing jewels
- 28,800 semi-oscillations per hour
- · Seconds stop function
- Shock resistant as per DIN ISO 1413
- Anti-magnetic as per DIN 8309

Case

- Case made of stainless steel, bead-blasted
- · Sapphire crystal glass in front, anti-reflective on both sides
- · Case back screw-fastened
- · Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- · Pressure-resistant up to 20 bar
- · Low pressure resistant

Functions

- · Hours, minutes, seconds
- Second time zone on a 24-hour basis
- Date display
- · Pilot's bezel with minute ratcheting and luminous key mark

SINN Technologies

- TEGIMENT Technology, therefore especially scratch-resistant
- Captive bezel
- · Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- · Temperature resistance technology, therefore functionally reliable at temperatures from minus 45°C up to 80°C

Dimensions and Weight

· Case diameter: 43 mm

• Band lug width: 22 mm

· Case thickness: 12 mm

• Weight without strap: 90 gramme

Dial and Hands

- Matte black dial
- · Numbers and indices coated with luminescent colour
- · Hour, minute and second hand coated with luminescent colour

Warranty

3 years