

756 S UTCPage 1 / 2
May 2024

The Duochronograph.



- · Case made of stainless steel
- Case made with Black Hard Coating on a TEGIMENT Technology basis
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 80,000 A/m
- Functionally reliable from -45 °C up to +80°C
- Sapphire crystal glass
- Nickel-free case back without TEGIMENT Technology
- Second time zone on a 12-hour basis
- · Pressure-resistant to 20 bar
- · Low pressure resistant

The 756 series pilot's watches unite all our core watchmaking competencies: these are instrument watches with a consistently functional design which honour the tradition of our navigation cockpit clocks.

The features of the 756 chronographs series include Magnetic Field Protection of up to 80,000 A/m, Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging, TEGIMENT Technology and therefore especially scratch-resistant, functionally reliable from -45 °C up to +80 °C and pressure resistance of up to 20 bar.



Technical details

Page 2 / 2 May 2024

Mechanical Movement

- Valjoux 7750 GMT
- · Self-winding mechanism
- · 25 bearing jewels
- 28,800 semi-oscillations per hour
- · Seconds stop function
- Shock resistant as per DIN ISO 1413
- Anti-magnetic as per DIN 8309

Case

- · Case made of stainless steel, black
- · Sapphire crystal glass in front, anti-reflective on both sides
- · Case back screw-fastened, nickel-free
- · Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- · Pressure-resistant up to 20 bar
- · Low pressure resistant

Functions

- · Hours, minutes
- · Second time zone on a 12-hour basis
- Date display
- Chronograph

SINN Technologies

- Black Hard Coating on a TEGIMENT Technology basis
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature resistance technology, therefore functionally reliable at temperatures from -45 °C up to +80°C
- · Magnetic Field Protection up to 80,000 A/m
- · Push-pieces with D3-System

Dimensions and Weight

• Case diameter: 40 mm

• Band lug width: 20 mm

Case thickness: 14 mm

· Weight without strap: 91 gramme

Dial and Hands

- Matte black dial
- · Number "12" and indices coated with luminescent colour
- · Hour, minute hand coated with luminescent colour

Warranty

3 years