

EZM 3F

The mission timer with Magnetic Field Protection and countdown bezel.



- Case made of stainless steel, bead-blasted
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 100mT (=80,000 A/m)
- Functionally reliable from -45°C up to $+80^{\circ}\text{C}$
- Pilot's bezel with minute ratcheting
- Crown on the left side of the case to prevent pressure on the back of the hand
- Sapphire crystal glass
- Nickel-free case back
- Mission timer design for optimal readability
- Water-resistant and pressure-resistant to 20 bar
- Low pressure resistant

The EZM 3F is a classic pilot watch, featuring a countdown pilot's bezel with minute ratcheting. For better readability, the two-way rotating bezel has a striking, luminous triangular main marker at 12 o'clock.

Also striking is the positioning of the crown on the left-hand side of the bead-blasted case. This enables greater freedom of movement and better protection for the crown. The instrumental watch is equipped with Ar-Dehumidifying Technology for more reliable functioning and greater freedom from fogging, Magnetic Field Protection up to 100mT (=80,000 A/m) and temperature resistance technology to ensure reliable functioning in a temperature range from -45°C to $+80^{\circ}\text{C}$.

Technical details

Page 2 / 2
May 2024

Mechanical Movement

• *The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information. ([further information](#))*

- SW200-1
- Self-winding mechanism
- 26 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Anti-magnetic as per DIN 8309

Case

- Case made of stainless steel, bead-blasted
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened, nickel-free
- Crown screwable
- Meet the technical requirements for water-resistance, as set out in standard DIN 8310
- Water-resistant and pressure-resistant to 20 bar
- Low pressure resistant

Functions

- Hours, minutes, seconds
- Date display
- Pilot's bezel with minute ratcheting and luminous key mark

SINN Technologies

- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature resistance technology, therefore functionally reliable at temperatures from -45°C up to +80°C
- Magnetic Field Protection up to 100mT (=80,000 A/m)

Dimensions and Weight

- Case diameter: 41 mm
- Band lug width: 20 mm
- Case thickness: 11.7 mm
- Weight without strap: 81 gramme

Dial and Hands

- Matte black dial
- Indices coated with luminescent colour
- Hour, minute and second hand coated with luminescent colour
- Mission timer design for optimal readability

Warranty

- 3 years