

## 756 UTC

The Duochronograph.

Page 1 / 2  
April 2024



- Case made of stainless steel, bead-blasted
- Case made with TEGIMENT Technology and therefore especially scratch-resistant
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Magnetic Field Protection up to 80,000 A/m
- Functionally reliable from -45 °C up to +80°C
- Sapphire crystal glass
- Nickel-free case back without TEGIMENT Technology
- Second time zone on a 12-hour basis
- Pressure-resistant to 20 bar
- Low pressure resistant

The 756 series pilot's watches unite all our core watchmaking competencies: these are instrument watches with a consistently functional design which honour the tradition of our navigation cockpit clocks.

The features of the 756 chronographs series include Magnetic Field Protection of up to 80,000 A/m, Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging, TEGIMENT Technology and therefore especially scratch-resistant, functionally reliable from - 45 °C up to + 80 °C and pressure resistance of up to 20 bar.

## Technical details

Page 2 / 2  
April 2024

### Mechanical Movement

- Valjoux 7750 GMT
- Self-winding mechanism
- 25 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Shock resistant as per DIN ISO 1413
- Anti-magnetic as per DIN 8309

### Case

- Case made of stainless steel, bead-blasted
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened, nickel-free
- Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Pressure-resistant up to 20 bar
- Low pressure resistant

### Functions

- Hours, minutes
- Second time zone on a 12-hour basis
- Date display
- Chronograph

### SINN Technologies

- TEGIMENT Technology, therefore especially scratch-resistant
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature resistance technology, therefore functionally reliable at temperatures from -45 °C up to +80°C
- Magnetic Field Protection up to 80,000 A/m
- Push-pieces with D3-System

### Dimensions and Weight

- Case diameter: 40 mm
- Band lug width: 20 mm
- Case thickness: 14. mm
- Weight without strap: 91 gramme

### Dial and Hands

- Matte black dial
- Number "12" and indices coated with luminescent colour
- Hour, minute hand coated with luminescent colour

### Warranty

- 3 years