

## T1

The Diving watch made of high-strength titanium with captive safety bezel.



- Case made of high-strength titanium, bead-blasted
- Tested based on European diving equipment standards and certified by DNV GL
- Waterproof and pressure-resistant to 1,000 m diving depth (= 100 bar), certified by DNV GL
- Captive Safety Diver's Bezel with guard to prevent accidental misadjustment
- Bezel with TEGIMENT Technology and therefore especially scratch resistant
- Arrow-shaped minute hand for clear reading of set time
- Colour-differentiated luminous paint for minute hand and key mark on the bezel for clear reading of set time
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Functionally reliable from – 45 °C up to + 80 °C
- Sapphire crystal glass
- Mission timer design for optimum readability
- Low pressure resistant

The T1 is our mission timer; all of the case parts are made from high-strength titanium, bead-blasted. Titanium is distinguished by its exceptionally low weight, extreme strength and superior resistance to seawater. It also offers a high degree of wearing comfort as it causes no allergies.

A further special feature of the T1 is the Captive Safety Diver's Bezel which is distinguished by two basic components: its secure attachment and rotation protection. More information on this can be found in the SINN Technologies section.

The arrow-shaped minute hand is being used here for the first time in one of our diver's watches. The set time is especially easy to read thanks to the different shapes of the hour and minute hands. To ensure that this is also possible in the dark or in adverse viewing conditions, the T1 also features colour-differentiated luminous paint for the minute hand and key mark on the bezel for clear reading of set time.

## Technical details

Page 2 / 3  
October 2021

### Mechanical Movement

• *The information on the mechanical movement corresponds to the current production situation in Frankfurt am Main. Due to technical changes, it may happen in individual cases that stock items of our sales partners deviate from this information. ([further information](#))*

- ETA 2892-A2
- Self-winding mechanism
- 21 bearing jewels
- 28,800 semi-oscillations per hour
- Seconds stop function
- Anti-magnetic as per DIN 8309

### Case

- Case made of titanium, bead-blasted
- Sapphire crystal glass in front, anti-reflective on both sides
- Case back screw-fastened, nickel-free
- Crown screwable
- Meet the technical requirements for waterproofness, as set out in standard DIN 8310
- Waterproof and pressure-resistant to 1,000 m diving depth (= 100 bar), certified by DNV GL
- According to the technical demands for the diving norm DIN 8306
- Tested based on European diving equipment standards EN 250 and EN14143, certified by DNV GL
- Low pressure resistant

### Functions

- Hours, minutes, seconds
- Date display
- Diver's bezel with minute ratcheting and luminous key mark
- Arrow-shaped minute hand for clear reading of set time
- Colour-differentiated luminous paint for minute hand and key mark on the rotating bezel for clear reading of set time

### SINN Technologies

- Bezel with TEGIMENT Technology, therefore especially scratch-resistant
- Captive safety bezel
- Ar-Dehumidifying Technology enhances functional reliability and freedom from fogging
- Temperature Resistance Technology, therefore functionally reliable at temperatures from – 45 °C up to + 80 °C

### Dimensions and Weight

- Case diameter: 45 mm
- Band lug width: 22 mm
- Case thickness: 12.5 mm
- Weight without strap: 71 gramme

### Dial and Hands

- Matte black dial
- Indices coated with luminescent colour
- Hour, minute and second hand coated with luminescent colour

# Sinn

SPEZIALUHREN ZU FRANKFURT AM MAIN

Page 3 / 3  
October 2021

## Warranty

- 3 years

SINN SPEZIALUHREN GMBH

Wilhelm-Fay-Straße 21 • 65936 Frankfurt am Main • Tel. +49 (0)69 / 97 84 14-0 • Fax +49 (0)69 / 97 84 14-201 • info@sinn.de • www.sinn.de  
Geschäftsführer: Dipl. Ing. Lothar Schmidt • Amtsgericht Frankfurt am Main • HRB 38841 • USt.-ID.: DE249383321 • WEEE-Reg.-Nr.: DE75393444